

ORACLE CONFIDENTIAL

“Express Mail” Mailing Label No. **EL960828108US**

PATENT APPLICATION
ATTORNEY DOCKET NO. OR03-11001

UNITED STATES UTILITY PATENT APPLICATION

FOR

CUSTOMIZABLE METADATA MERGING
FRAMEWORK

INVENTORS:

Rajagopal Baskaran and Jaime E. Singson

Oracle Corporation
500 Oracle Parkway
Redwood Shores, CA 94065

Attorney Docket No. OR03-11001
EJG E:\ORACLE CORPORATION\OR03-11001\OR03-11001 APPLICATION.DOC
Oracle Matter No. OID-2003-110-01

Inventors: Baskaran et al..

CUSTOMIZABLE METADATA MERGING FRAMEWORK

5 **Inventors:** Rajagopal Baskaran and Jaime E. Singson

BACKGROUND

10 **Field of the Invention**

 [0001] The present invention relates to metadata that is used to define objects in databases. More specifically, the present invention relates to a method and an apparatus that facilitates merging metadata associated with different versions of objects of a database in a customizable manner.

15

Related Art

 [0002] Databases typically form the backbone of modern electronic business solutions. As business requirements change over time or are modified to meet local requirements, corresponding modifications may need to occur in the structure of an underlying database. These modifications can cause different versions of the same database to diverge over time. This can cause problems when divergent versions of a database need to be subsequently reconciled or updated.

20

 [0003] Database objects are typically defined using metadata. The properties, attributes, and relationship of a database object with other database objects can be described using the unified modeling language (UML). The

25

structure of metadata can be modeled using UML (Unified Modeling Language) to define a series of classes, associations, and attributes. For instance, a Table is a Class, a Column is a Class, and a Partition is a Class. 'Name' is an Attribute that exists for a Table, Column, and a Partition Class. A relationship exists between
5 Table and Column (a table owns a column), and so we say there is an Association between the Table Class and Column Class. An end user typically receives metadata that defines a database object, for example a table, from a solutions provider. After receiving this metadata, the end user can typically customize the metadata to change the structure of the metadata object. For example, an end user
10 may customize the metadata to add an additional column to a table or to change a property of the table.

[0004] It is possible for different end users to customize the same metadata in different ways. For example, end users in a multi-national corporation located in different jurisdictions may customize metadata to allow a
15 corresponding database to accommodate specific data items required by their local jurisdictions.

[0005] In some circumstances, it is desirable to merge different versions of metadata. For example, a solutions provider may generate a new version of the metadata to enhance the database object, or management may want the metadata
20 for two or more databases to be merged. This merging process is presently performed manually, and consequently involves a significant amount of time and effort.

[0006] Hence, what is needed is a method and an apparatus that facilitates merging different versions of a database without the problems described above.

25

SUMMARY

5 [0007] One embodiment of the present invention provides a system that facilitates merging different versions of a database object. During operation, the system receives metadata associated with a first version of a database object and a second version of the database object. The system then compares metadata associated with the first version with metadata associated with the second version to create a difference report. Next, the system uses the difference report to create an action plan that specifies how to merge the metadata associated with the first and second versions of the metadata object.

10 [0008] In a variation of this embodiment, metadata associated with the database objects are represented in Unified Modeling Language (UML).

 [0009] In a further variation, comparing the metadata associated with the first and second versions of the database object involves allowing a user to specify which associations of the database object needs to be compared.

15 [0010] In a further variation, comparing the metadata associated with the first and second versions of the database object involves allowing the user to specify how to compare the metadata for each association in the database object.

 [0011] In a further variation, creating the action plan involves allowing a user to select which actions to take in merging the metadata in order to produce merged metadata with the desired properties and attributes.

 [0012] In a further variation, creating the action plan involves examining the difference report to determine what actions to take in bringing the metadata associated with the first version and second versions of the database object into agreement.

25 [0013] In a variation of this embodiment, the metadata associated with the first and second versions of the database object can define Oracle database objects

like Dimensions, Cubes, Tables, Views, Materialized views, Transformations, and their associated objects. An example of associated objects is that Column, Foreign Keys, and Unique Keys can be associated with table metadata definition. Oracle is a trademark or registered trademark of Oracle International Corporation.

5 **[0014]** In a variation of this embodiment, the action plan can specify a number of actions including creating, updating, and deleting of database objects.

BRIEF DESCRIPTION OF THE FIGURES

10 **[0015]** FIG. 1 illustrates a metadata exchange framework in accordance with an embodiment of the present invention.

[0016] FIG. 2 illustrates the process of creating a difference report from compatible objects in accordance with an embodiment of the present invention.

15 **[0017]** FIG. 3 illustrates the process of creating a difference report from non-compatible objects in accordance with an embodiment of the present invention.

[0018] FIG. 4 illustrates the process of creating an action plan and a merged object in accordance with an embodiment of the present invention.

[0019] FIG. 5 illustrates source and target objects in accordance with an embodiment of the present invention.

20 **[0020]** FIG. 6 illustrates a difference report in accordance with an embodiment of the present invention.

[0021] FIG. 7 illustrates an action plan in accordance with an embodiment of the present invention.

25 **[0022]** FIG. 8 presents a flowchart illustrating the process of merging metadata associated with a first object and a second object in accordance with an embodiment of the present invention.

DETAILED DESCRIPTION

[0023] The following description is presented to enable any person skilled in the art to make and use the invention, and is provided in the context of a particular application and its requirements. Various modifications to the disclosed
5 embodiments will be readily apparent to those skilled in the art, and the general principles defined herein may be applied to other embodiments and applications without departing from the spirit and scope of the present invention. Thus, the present invention is not intended to be limited to the embodiments shown, but is to be accorded the widest scope consistent with the principles and features
10 disclosed herein.

[0024] The data structures and code described in this detailed description are typically stored on a computer readable storage medium, which may be any device or medium that can store code and/or data for use by a computer system. This includes, but is not limited to, magnetic and optical storage devices such as
15 disk drives, magnetic tape, CDs (compact discs) and DVDs (digital versatile discs or digital video discs), and computer instruction signals embodied in a transmission medium (with or without a carrier wave upon which the signals are modulated). For example, the transmission medium may include a communications network, such as the Internet.

Metadata Exchange Strategy Framework

[0025] FIG. 1 illustrates a metadata exchange strategy framework 102 in accordance with an embodiment of the present invention. Metadata exchange strategy framework 102 includes metadata change manager 110, metadata
25 exchange strategy 112, and execution engine 114. Metadata change manager 110 provides functions for creating difference reports, such as difference report 108, as

described below in conjunction with FIGs. 2, 3, 5, and 8. Metadata exchange strategy 112 provides functions for creating an action plan, such as action plan 113, as described below in conjunction with FIG. 4, 6, 7, and 8. Execution engine 114 provides functions for executing the action plan as described below in conjunctions with FIGs. 4 and 8

[0026] Metadata exchange strategy framework 102 accepts source object 104 and target object 106 and creates merged object 108. Source object 104, target object 106, and merged object 108 contain metadata describing respective database objects. Source object 104 and target object 108 are descriptions of the same database object that differ, possibly because their metadata definition may have been updated or customized by different users.

[0027] Source object 102 and target object 106 are typically Oracle database objects and not just tables and columns (i.e. cubes, transformations, and the like). Also source object 102 and target object 106 may include other objects such as files in a file system or records in a file that have been captured using UML and stored in the database during design time. This is typically achieved by having a table called "file" and a table called "record." The metadata of external table objects refers to the record metadata in the record table. These are not database objects, but still dictate the structure of some database objects. For example the structure of an external table is dictated by the file and record that it is referring to. Hence, there exists a requirement that external tables have to be merged from the record during design time, although record is not a database object. Hence, this is not just restricted to database objects but also to others that are marked in UML and stored in the database as classes, attributes, and associations.

Difference Report

5 [0028] FIG. 2 illustrates the process of creating a difference report from compatible objects in accordance with an embodiment of the present invention. Metadata change manager 110 receives external tables 202 and 204 and creates a difference report 208, which describes the differences between external tables 202 and 204. For example, external tables 202 and 204 contain metadata describing the same object that differ possibly because one of the external tables is an updated version of the other external table, or because the external tables have been customized by different individuals.

10

Difference Report from Non-Compatible Objects

15 [0029] FIG. 3 illustrates the process of creating a difference report from non-compatible objects in accordance with an embodiment of the present invention. In the example illustrated in FIG. 3, a difference report between external table 202 and record 302 is desired. Note that external table 202 may have been originally created from record 302.

20 [0030] Adapter 304 first converts record 302 into compatible external table 306. Metadata change manager 110 then receives external tables 202 and 306 and creates a difference report 308, which describes the differences between external tables 202 and record 302, which are ultimately the differences between external table 202 and record 302.

Action Plan and Merged Object

25 [0031] FIG. 4 illustrates the process of creating an action plan and a merged object in accordance with an embodiment of the present invention. Metadata exchange strategy 112 receives a difference report 208 created by

metadata change manager 110. During this process, metadata exchange strategy 112 is used to examine difference report 208 and to create an action plan 404 for merging the two objects used in creating difference report 208.

5 [0032] Next, execution engine 114 receives action plan 404. After a user selects which items of action 404 are to be performed, execution engine 114 creates merged object 108.

[0033] Creation of an action plan requires the user to specify if a merge or a replace plan is preferred. The replace plan means deleting everything from the target the does not have a match in the source, while the merge plan would not
10 allow deletion of anything from the target.

[0034] After the action plan has been created, the user can customize the action plan to apply the specific actions that are desired. Applying the action plan causes creation, deletion, or updates of the target object. Also, the user has the ability to specify which attributes in the target that need to be3 updated in the
15 event of create or update in the target. The user can also change the values to suit the required needs. This is determined at the time when the user wants to execute the created action plan.

Source and Target Objects

20 [0035] FIG. 5 illustrates source and target objects in accordance with an embodiment of the present invention. These source and target objects include metadata for table 508 and table 502, respectively, and originated from the same metadata. Source table 508 includes a description 509 of table 508. Additionally, source table 508 is associated with columns 512 and properties 510.
25 Properties 510 include property 2 and property 3, and columns 512 include

column 1, column 2, and column 3. Together, table 508, properties 510, and columns 512 describe a corresponding database table.

[0036] Target table 502 includes a description 503 of table 502.

Additionally, target table 502 is associated with columns 506 and properties 504.

5 Properties 504 includes property 1, and columns 506 include column 1 and column 2. Together, table 502, properties 504, and columns 506 describe a corresponding database table. Note that any mapping between columns 506 of table 502 and columns 512 of table 508 is possible. For example, column 1 of columns 506 and column 2 of columns 512 may refer to the same data, while
10 column 2 of columns 506 and column 1 of columns 512 may also refer to the same data.

Difference Report

[0037] FIG. 6 illustrates a difference report 208 in accordance with an
15 embodiment of the present invention. Note that there are many ways to compare different components of the metadata. In this example, tables are being compared by name, columns are being compared by position, and properties are being compared by name.

[0038] Difference report 208 includes data for the parameters being
20 compared, in this example table name, column position, and properties. The comparison of the table names indicates that the target and source have the same name; therefore the input into the action plan is to update the table.

[0039] The comparison of the columns indicates that column 1 in the
target includes the same data as column 2 in the source and that column 2 in the
25 target includes the same data as column 1 in the source. The input to the action plan is to update the column descriptions. Since column 3 exists in the source but

not in the destination, the input to the action plan is to create column 3 in the target.

5 [0040] The comparison of the properties indicates that property 1 exists in the target but not in the source, while properties 2 and 3 exist in the source but not in the destination. The action plan for the properties includes deleting property 1 and creating properties 2 and 3. These actions will bring the target into alignment with the source if the user selects all of the actions as described below in conjunction with FIG. 7.

10 **Action Plan**

 [0041] FIG. 7 illustrates an action plan 404 in accordance with an embodiment of the present invention. Action plan 404 includes actions derived from difference report 208 described above in conjunction with FIG. 6. Each line of action plan 404 includes a checkbox 702, a description of the action 704, and
15 an action 706. A user can select which actions are required by checking the checkbox in column 702. After the user checks the actions, execution engine 114 performs the checked actions.

Merging Metadata

20 [0042] FIG. 8 presents a flowchart illustrating the process of merging metadata associated with a first object and metadata associated with a second object in accordance with an embodiment of the present invention. The system starts when a first metadata associated with the first version of an object is received (step 802). Next, the system receives the second metadata associated
25 with the second version of the object (step 804). Note that steps 802 and 804 can

occur in the opposite order or simultaneously. If needed, the system converts the second metadata to be compatible with the first metadata (step 806).

5 **[0043]** After receiving the first metadata and the second metadata, the system examines the first metadata and the second metadata to create a difference report (step 808). The system then creates an action plan from the difference report (step 810).

10 **[0044]** Next, the system allows a user to select portions of the action plan to implement by checking checkboxes in the action plan (step 812). Finally, the system uses the selected actions to merge the first metadata and the second metadata to create merged metadata (step 814).

15 **[0045]** The foregoing descriptions of embodiments of the present invention have been presented for purposes of illustration and description only. They are not intended to be exhaustive or to limit the present invention to the forms disclosed. Accordingly, many modifications and variations will be apparent to practitioners skilled in the art. Additionally, the above disclosure is not intended to limit the present invention. The scope of the present invention is defined by the appended claims.